



FPC(UK) Ltd Manufacturers and suppliers of quality **FIRESURE**® Fire Protection Products.

Tel:- 01384 633660

www.fpc-uk.com Email:- sales@fpc-uk.com

Home of **FIRESURE**® 'Fire Protection Certified', range of products .

PUTTY PAD & Packs Intumescent Liner Range

[Data Sheet 10001/B](#)

Description

The **FIRESURE**™ Putty Pads for Sockets, Switches, pipe sealing and water tap sealing have been designed to prevent the passage of fire through the socket and switch boxes and will reinstate the fire rating of the partition for up to two hours. It also has good sound insulation properties.

The Putty Pad is a non-setting, flexible, hand workable, re-useable and re-seviceable product due to its non-setting properties. They can be fitted inside (90% sales) or externally around the boxes, around pipes and water taps. In a fire they form a robust char which prevents the fire breaking through the boxes. Socket boxes are two sizes for internal use and two sizes for external use. The FPC range of **FIRESURE**® is probably the only range backed by **Failure to perform insurance** called **Efficacy insurance** (or 'failure to perform' cover) protects you against the legal liability for injury to third parties, or damage to third party property, when a product or service you supply fails to perform its intended function subject to being fitted all in accordance with specified installation details and within the tested scope of application. Covered up to £10,000,000.00 .

Features and Benefits

120 minute Fire Tested to the relevant parts of EN 1366-3:2004

Sound insulating to BS EN ISO 140-3:1995

Result: 67 (-2.-7)Rw(C:C_{tr}) (dB)

Calculated to BS EN ISO 717-1:1997

Provides a full fire barrier for switches and sockets

Up to 2 hour Fire Rated

Can be used for all dry lining applications

Easy to install - no screws, fixing

Cost effective

Available in 2 sizes – single and double

Unaffected by moisture

Non-toxic



Product Code	Type	Size (mm)	Thickness (mm)	Suitable for:
PP1S	Internal	170 x 170	3mm nominal	Single Gang socket/switch box
PP2D	Internal	230 x 170	3mm nominal	Double Gang socket/switch
PP1SX -	External	Rectangular	3mm nominal	Single Gang socket/switch box
PP2DX	External	Rectangular	3mm nominal	Double Gang socket/switch box
Product Code	Type	Size (mm)	Thickness (mm)	Suitable for:
PPC5	Cord	15mm OD	15mm OD	Sealing round metal/copper pipe & duct
PPWB2		Cut pad	3mm nominal	External Sealing round watertap/box Red
PPMBSETA	Internal	mixed	3mm nominal	10 ref PP1S & 10PP2D in trade pack
PPMBPLAY	Internal/ Extenal	Mix counter display box	3mm nominal +15mm OD	10 each PP1S & 10PP2D + 10 PPWB2 + 1 box PPC5 in a counter display box